

■ Single Row QPL Ordering Guide

Examples:

M32139-01-A-01-S-N Bi-Lobe Male, 9 contacts, 6.0" White 30 AWG wire, Jackscrew, Aluminum shell, Nickel-Plated

M32139-02-A-04-T-N Bi-Lobe Female, 21 contacts, 6.0" Colored AWG wire, Threaded Hole, Aluminum Shell, Nickel-Plated

(Each option separated by a hyphen)

Basic Spec	Slash Number	Wire Type	Hardware	Shell Material and Finish	Space Class
M32139	Plugs 01-A - Pin Connector, 9 Contacts Single 01 - B-Pin Connector, 15 Contacts Single 01 - C-Pin Connector, 21 Contacts Single 01 - D-Pin Connector, 25 Contacts Single 01 - E-Pin Connector, 31 Contacts Single 01 - F-Pin Connector, 37 Contacts Single 01 - G-Pin Connector, 51 Contacts Single Receptacles 02 - A-Socket Connector, 9 Contacts Single 02 - B-Socket Connector, 15 Contacts Single 02 - C-Socket Connector, 21 Contacts Single 02 - D-Socket Connector, 25 Contacts Single 02 - E-Socket Connector, 31 Contacts Single 02 - F-Socket Connector, 37 Contacts Single 02 - G-Socket Connector, 51 Contacts Single	NEMA HP-3-ETXBBB Wire <i>(#30 Awg, 7 Strand Silver-Coated Cooper, Extruded PTFE Insulation, 250 V rms, 200° C.)</i> 01 - 6 inches White 02 - 18 inches White 03 - 36 inches White 04 - 6 inches 10 Color Repeat 05 - 18 inches 10 Color Repeat 06 - 36 inches 10 Color Repeat M22759/33-30 Wire <i>(#30 Awg, 7 Strand Silver-Coated High-Strength Cooper, Extruded Cross-Linked Modified ETFE Insulation, 600 V rms, 200° C.)</i> 07 - 6 inches White 08 - 18 inches White 09 - 36 inches White 10 - 6 inches 10 Color Repeat 11 - 18 inches 10 Color Repeat 12 - 36 inches 10 Color Repeat Composite PTFE/Polyimide Wire <i>(#30 Awg, 7 Strand Silver-Coated High-Strength Cooper, Extruded Cross-Linked Modified ETFE Insulation, 600 V rms, 200° C.)</i> 13 - 6 inches White 14 - 18 inches White 15 - 36 inches White 16 - 6 inches 10 Color Repeat 17 - 18 inches 10 Color Repeat 18 - 36 inches 10 Color Repeat	S  Jackscrew, #0-80, Hex Head (Slash 01 & 03 Pin Connectors Only)	 CD Aluminum Shell, Cadmium Plated	S Space Class (Not For Use With Cadmium Plated Aluminum Shells) Omit for Non-Space Applications
			V  Threaded Hole, #0-80 (Slash 02 & 04 Socket Connectors Only)	 N Aluminum Shell Electroless Nickel Plated	
			RH RoHS COMPLIANT 	 S Stainless Steel Shell Passivated	
				 T Titanium Shell Unplated	