


Bi-Lobe®

Straight Tail Type DD

Dual Row Straight Tail (Type DD) Ordering Guide

■ Series	■ # of Contacts	■ Termination Type	■ Shell Material and Finish	■ Options
■ MNPO Male (Pin Connector)	09 15 21 25 31 37 51 65	DD Thru-Hole Straight	 N Aluminum Shell, Electroless Nickel Plated  CD Aluminum Shell, Cadmium Plated  B Aluminum Shell, Black Anodized  S Stainless Steel Shell, Passivated  T Titanium Shell Unplated	 ETH End Threaded Hole #0-80  EJS End Jackscrew (Pin Only)  M Mounting Hole  HTE High Temp. Epoxy
■ MNSO Female (Socket Connector)				

Examples



MNPO-25-DD-N-EJS

MNSO-37-DD-N-ETH-HTE



■ Straight Through Hole Bi-Lobe® Mass Chart (estimated +/- 10%)

■ Pin Count	Male Aluminum	Male Titanium	Male Stainless Steel	Female Aluminum	Female Titanium	Female Stainless Steel
■ 09	.41 g	.50 g	.66 g	.33 g	.52 g	.86 g
■ 15	.46 g	.56 g	.73 g	.39 g	.59 g	.96 g
■ 21	.51 g	.61 g	.81 g	.44 g	.66 g	1.06 g
■ 25	.55 g	.65 g	.86 g	.48 g	.71 g	1.12 g
■ 31	.60 g	.71 g	.93 g	.54 g	.78 g	1.22 g
■ 37	.65 g	.76 g	1.01 g	.59 g	.85 g	1.32 g
■ 51	.76 g	.90 g	1.18 g	.72 g	1.02 g	1.55 g
■ 65	.88 g	1.03 g	1.36 g	.86 g	1.19 g	1.78 g