

Bi-Lobe®

Panel Mount Type AA-DD-FF-WD

Panel Mount (Type AA-DD-FF-WD) Ordering Guide

Termination

Wire Length

Shell Material and Finish

Options

Series	# of Contacts	Type	Length	Shell Material and Finish	Options
MNSOP	09	DD	XX.X	N	ETH
Panel Mount (Socket Connector)	15	Straight Thru Hole	Length in Inches	Aluminum Shell, Electroless Nickel Plated	End
	21			CD	Threaded Hole, #0-80
	25				
	31	WD		Aluminum Shell, Cadmium Plated	M
	37	Pre-Wired			Mounting Hole (Type AA Only)
	51	PTFE		B	
	65				
		AA		S	C
		Horizontal Surface Mount		Stainless Steel Shell, Passivated	Color Coded
		FF		T	HTE
		Flex Mount		Titanium Shell Unplated	High Temp. Epoxy

Examples



MNSOP-25-WD-1.0-N-ETH-C



MNSOP-37-FF-N-ETH-HTE



RH
RoHS
COMPLIANT

49

Panel Mount Bi-Lobe® Mass Chart (estimated +/- 10%)

Pin Count	Female Aluminum	Female Titanium	Female Stainless Steel	Additional Mass of 30 AWG Wire (g/in)
09	.49 g	.78 g	1.31 g	.22 g
15	.56 g	.87 g	1.44 g	.37 g
21	.63 g	.97 g	1.57 g	.52 g
25	.68 g	1.03 g	1.66 g	.62 g
31	.75 g	1.12 g	1.79 g	.77 g
37	.82 g	1.22 g	1.92 g	.92 g
51	.99 g	1.43 g	2.23 g	1.27 g
65	1.16 g	1.65 g	2.53 g	1.62 g