

# Bi-Lobe®

## Straight Tail Type DD

### ■ Single Row Straight Tail (TYPE DD)

■ Series	■ # of Contacts	■ Termination Type	■ Shell Material and Finish	■ Options
■ MBPS Male (Pin Connector)	05	DD	N	
	09	Straight	Aluminum Shell, Electroless Nickel Plated	
	15	Thru-Hole	CD	
	21		Aluminum Shell, Cadmium Plated	
	25		B	
	31		S	
	37		T	
■ MBSS Female (Socket Connector)	51			
 				
Examples				
 				
MBPS-25-DD-N-EJS		MBSS-37-DD-N-ETH-HTE		

### ■ Straight Thru-Hole Bi-Lobe® Mass Chart (estimated +/- 10%)

■ Pin Count	Male Aluminum	Male Titanium	Male Stainless Steel	Female Aluminum	Female Titanium	Female Stainless Steel
■ 5	.42 g	.53 g	.72 g	.34 g	.55 g	.94 g
■ 9	.49 g	.62 g	.85 g	.42 g	.66 g	1.10 g
■ 15	.58 g	.75 g	1.04 g	.53 g	.82 g	1.35 g
■ 21	.68 g	.87 g	1.23 g	.64 g	.98 g	1.59 g
■ 25	.74 g	.96 g	1.36 g	.72 g	1.09 g	1.76 g
■ 31	.84 g	1.09 g	1.55 g	.83 g	1.25 g	2.01 g
■ 37	.93 g	1.22 g	1.74 g	.95 g	1.41 g	2.25 g
■ 51	1.16 g	1.52 g	2.18 g	1.21 g	1.79 g	2.83 g