







# Micro-D

## Standard Micro-D

### ■ Metal Shell Micro-D Connector Saver (TYPE Z)

Series	# of Contacts	Shell Material and Finish	Hardware	Options
<b>MMD</b> <b>Z- CONNECTOR</b> <b>SAVER</b>	<b>009</b>	 <b>N (STD)</b> Aluminum Shell, Electroless Nickel Plated	<b>00</b> - NONE, .092 HOLE (STD)	<b>HTE</b> High Temp. Epoxy
	<b>015</b>			
	<b>021</b>	 <b>C</b> Aluminum Shell, Cadmium Plated	<b>01</b> - FIXED JACK- POSTS (STD)	
	<b>025</b>			
	<b>031</b>	 <b>B</b> Aluminum Shell, Black Anodized	<b>11</b> - COMBO JACKPOST/ JACKSCREW (FEMALE JACK- POST) (STD)	<b>RH</b> RoHS COMPLIANT
	<b>037</b>			
	<b>051*</b>	 <b>P</b> Stainless Steel Shell, Passivated	<b>12</b> - COMBO JACKPOST/ JACKSCREW (MALE JACK- POST) (STD)	

\*(Use 512 for  
Two Row 051  
and 513 for  
Three Row 051)

#### Example



MMDZ-025-N00-HTE

